

B-36B Specs



Hydrostatic Riding Trencher Specifications Sheet

ENGINE

| | |
|--------------|-----------------------------------|
| Make/Model | Kubota V2203 |
| HP | 46 @ 2,800 RPM |
| Fuel/Cooling | Diesel/Liquid |
| Fuel Tank | 10 U.S. gallons |
| Displacement | 134.08 in. ³ (2,197cc) |
| Cylinders | 4 |

TRACTION DRIVE

| | |
|-------------------------|------------------------------|
| Traction Drive | Hydrostatic |
| Vehicle Speed-Transport | 0 - 5.3 MPH (0-8 KPH) |
| Vehicle Speed-Trenching | 0 - 2.6 MPH (0-4 KPH) |
| Parking Brake | Caliper |
| Traction Control | Single Lever (servo control) |
| Transfer Case | Fully Enclosed, Lubricated |
| Tire Size | 26 x 12 - 12, 8 Ply Rating |




CHAIN DRIVE

| | |
|---------------------------|--|
| Trench Widths (min.-max.) | 6 in to 12 in (152-305 mm) |
| Trench Depths (min.-max.) | Adjustable 3', 4', 5' (90, 120, 155 cm) |
| Attachment Positions | Centerline 15 in RH Offset (38 cm) 30 in RH Offset (76 cm) |
| Chain Drive | Hydrostatic, Variable |
| Chain Speed | 0 - 530 FPM (1-162 MPM) |
| Spoil Handling | Adjustable, Dual Auger |
| Auger Size (Optional) | 12"D x 15" long (30 cm x 38 cm) 12"D x 29" long (30 cm x 74 cm) |
| Chain Pitch | 2.00 in |

GENERAL SPECS

| | |
|-------------------------------|----------------------|
| Operating Weight (w/trencher) | 4,600 lbs (2,080 kg) |
| Turning Radius | 120 in (290 cm) |
| Standard Backfill Blade | 6-way Parallelogram |

- [Home](#)
- [The Company](#)
- [Trenchers/Plows](#)
- [Services](#)
- [Contact Us](#)
- [Press Room](#)
- [Factory Tour](#)
- [Site Map](#)



Note: Specification and design are subject to change without notice. All dimensions shown in inches. Respective metric dimensions are enclosed in parenthesis.